

# Quality assured by European standards

The majority of steel constructions are composed with non-preloaded construction bolts. Non-preloaded bolt connections must meet EN 15048, in which part 1 describes the general requirements and part 2, the suitability test. That's why Stafa has access to an extensive and comprehensive stock of construction bolts that meet EN 15048-1. The manufacturer guarantees that the bolt/nut assemblies they supply meet the specifications set by this standard.

## **EN 15048 requirements**

- Bolts and nuts shall be packed and supplied in the original and unopened box.
- ✓ Bolts and nuts in a single connection must originate from one and the same manufacturer.
- Surface treatments on the bolts and nuts may only be applied under the manufacturer's supervision.

# EN 15048 marking of nuts and bolts

- ✓ Property class marking
- ✓ Special marking "SB" (Structural Bolting)
- ✓ Identification mark of the manufacturer of the assembly

### The label includes:

- CE marking
- ✓ Lot number
- ✓ Reference to EN 15048-1
- ✓ "SB" marking
- Identification number of the certified authority and manufacturer
- ✓ Dimension
- ✓ Property class marking
- Product designation (ISO standard for bolts
  ISO 4014 or 4017 and nuts ISO 4032)



### ISO 4014 + 4032 / 8.8

Ø	ø 10		12		14		16		18		20		24		27	30	36
	NZ	HDG	NZ	HDG	ZN	HDG	NZ	HDG	NZ	HDG	NZ	HDG	NZ	HDG	HDG	HDG	HDG
50	•	•	•	•				•									
55				•			•	•									
60	•	•	•	•	•	•	•	•	•	•		•					
65							•	•			•	•					
70	•	•	•	•	•	•	•	•	•	•	•	•		•			
75												•					
80	•	•	•	•	•	•	•	•	•	•	•	•	•	•			
90	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	
100	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
110		•	•	•			•	•			•	•	•	•	•	•	
120		•	•	•	•	•	•	•			•	•	•	•	•	•	•
130		•	•	•			•	•			•	•	•	•	•	•	•
140		•	•	•			•	•			•	•	•	•	•	•	•
150		•	•	•			•	•					•	•	•	•	•
160		•	•	•			•	•			•	•	•	•	•	•	•
170			•	•													
180		•	•	•			•	•			•	•	•	•	•	•	•
190			•	•				•									
200		•		•			•	•			•	•	•	•	•	•	•
220				•				•				•		•		•	•
240								•				•		•		•	•
260								•				•		•		•	
280								•				•				•	
300								•				•				•	

### ISO 4017 + 4032 / 8.8

Ø	10		12		14		16		18		20		24		27	30	36	
	NZ	HDG	HDG	HDG	HDG													
20	•	•	•	•														
25	•	•	•	•			•	•										
30	•	•	•	•	•	•	•	•										
35	•	•	•	•	•	•	•	•										
40	•	•	•	•	•	•	•	•	•	•	•	•						
45	•	•	•	•	•	•	•	•	•	•	•	•						
50	•	•	•	•	•	•	•	•	•	•	•	•	•	•				
55							•	•			•	•						
60			•	•			•	•	•	•	•	•	•	•	•			
65							•	•										
70			•	•			•	•			•	•	•	•	•	•		
75																		
80			•	•			•	•			•	•	•	•	•	•		
90							•	•			•	•	•	•	•	•	•	
100							•	•			•	•	•	•	•	•	•	
110																	•	
120																•	•	
120																•	•	

Den Engelsman 18
 6026 RB Maarheeze
 The Netherlands

+31 495 599 888

■ info@stafa.nl

stafa.nl

More information: stafa.nl